Hanse Handwerks Haus GbR
Schragenberg 26
21640 Nottensdorf
Tel. 04163833930
info@klimacorner.de
https:www.klimacorner.de

klimacorner.de

PRODUCT DATA SHEET · ISSUE DATE 2026-11-09

Aeroline Terra PEX Rubber end cap 25 x 2.3/32 x 2.9/40 x 3.7 mm

Item number: 96 003 68 · Brand: nmc



Technical data

Contents

Underground laid pipes of underground laid pipes	8				
Masonry sealing set	3.6.2	Install masonry sealing set			12

Fixed point clamp

Technical changes, errors, typographical and printing errors excepted.	3				

technical data to be found in.

Medium pipe (PE	-	Xa plastic pipe)	25 x 2,3	32 x 2,9	40 x 3,7
Max. perm.	Operating pressure at 95°C	6			
Temperature range	bis +90 °C				
Liquid pipe connection	0,65 l/m	1,0	6	l/m	1,77 l/m
Linear expansion coefficient	0,14 mm/(m K)				

Jacket pipe

Outer diameter	160 mm

Minimum bend radius	425 mm				

Sensor lines

Ring stiffness according to DIN 16961 (pipe series 4)	S	R24	≥ 16,0 kN/m		
Outer diameter	32 mm				
Inner diameter	2	5			
Thermal conductivity at +40°C	λ	40°c	= 0,0	40	W/mK
Thermal conductivity at 0°C	λ	0°c	= 0,03	6	W/mK
Insulation thickness	20 mm	13 mm			
Technical changes, errors, typographical and printing errors excepted.	5				

following core bore diameters required:

PEX	TERRA WP	Ø 200 mm (+2/	-	1mm)	, free from voids

Insert liner pipes into the wall penetration.

PEX	TERRA WP	Wall penetration Ø 250 mm & liner pipe Ø 200 mm

Concrete liner pipes in place with formwork.

PEX TERRA WP	Liner pipe Ø 200 mm concrete in place with formwork

remove immediately before covering.

Technical changes, errors, typographical and printing errors excepted.	7

Dimensions (W × H × D)

Technical changes, errors, typographical and printing errors excepted.	9									
with	plugs	bis	45	Diameter	drawn	are.	In	tilting	integrated	electrical in

conductor slider fixed.

Technical changes, errors, typographical and printing errors excepted.	11

First insert the pipe passages of the rubber cap onto the

cut to length according to corresponding pipe diameter (stage I	PEX 40,
stage II	PEX 32, stage III: PEX 25).

pull over the jacket pipe.

Technical changes, errors, typographical and printing errors excepted.	13

observe.

Technical changes, errors, typographical and printing errors excepted.	15

nmc Deutschland GmbH

Tel.:	+49-731-93292-0

Item data

Material	Plastic
Manufacturer article number	3053269
EAN	5413256106290
Brand	nmc

Source: manufacturer's data: Datenblatt · Technische Daten des Artikels (Lieferantendaten).
Own product data sheet based on the manufacturer's data; values transferred unchanged. The energy label and the EU product information sheet (EPREL) are authoritative for energy labelling. Errors and technical changes by the manufacturer excepted.